



grael[®]
psg

Industry-leading amplifier optimized
for Gold Standard HD PSG studies.

Over 25 years of experience in designing PSG and EEG amplifiers, including the highly successful E-Series, has culminated in **GraeL PSG**. Based on the flagship GraeL amplifier, the GraeL PSG has a channel subset dedicated for Sleep studies. A true-HD PSG amplifier with channels as specified for the *Gold standard AASM Type 1 studies*.

HD PSG

Technical specifications

DIMENSIONS

Grael System Component	Size L x W x H	Weight
Amplifier	240mm x 144mm x 50mm 9.45in x 5.66in x 1.97in	700 grams 24.7 ounces

NETWORK

POE (power over Ethernet)

NETWORK CONNECTION

Drop in cradle for quick disconnect

ANALOGUE TO DIGITAL CONVERTER

24 bit resolution

DATA SAVE RATE

256, 512, 1024, 2048 sps

SAMPLE RATE

16384 sps

PATIENT CONNECTIONS

CF as per IEC60601-1

SAFETY

IEC60601-1

EMC

IEC60601-1-2

COMMUNICATION INTERFACE

Network Type 802.3/802.3u twisted pair
Ethernet with auto MDIX
Supports IPV4 with DHCP, TCP, UDP, ICMP and ARP protocols

13 REFERENTIAL CHANNELS

Range $\pm 300\text{mV}$ (resolution $< 50\text{nV}$)
Frequency response DC to 580 Hz (user adjustable)
Input impedance $> 100\text{M}$
CMRR $> 100\text{dB}$
Noise (0.1 to 70Hz) $2\mu\text{Vpp}$ typical

6 DIFFERENTIAL CHANNELS

Range $\pm 300\text{mV}$ (resolution $< 50\text{nV}$)
Frequency response DC to 580 Hz (user adjustable)
Input impedance $> 20\text{M}$
CMRR $> 100\text{dB}$
Noise (0.1 to 70Hz) $2\mu\text{Vpp}$ typical

2 RESPIRATORY INDUCTIVE PLETHYSMOGRAPHY CHANNELS

Sensor Inductive band
Frequency response DC to 64 Hz

PRESSURE

Differential input 2 male luer
Range $\pm 100\text{cmH}_2\text{O}$
Frequency response DC to 580 Hz (user adjustable)
Accuracy $\pm 1\text{cmH}_2\text{O}$ at 25°C

POSITION

Sensor Tri-axial accelerometer
Positions Supine, prone, left, right, upright

MICROPHONE

Sensor Electret
Frequency response 5 to 580 Hz (user adjustable)

LIGHT

Sensor Integrated

OXIMETER

SP02 range 25 to 100%
Heart rate range 35 to 300 pulses per minute
SP02 accuracy 70 – 100% ± 2.5 digits within 1 standard deviation
Heart rate accuracy $\pm 1\%$ ± 1 digit

Sample rate (SP02, HR, status) 1 sample per second, up sampled to match the other channels
Sample rate (plethysmograph) 256 samples per second, up sampled to match the other channels

ENVIRONMENTAL REQUIREMENTS

Temperature Ambient operating temperature range: $0^\circ\text{C} - 40^\circ\text{C}$ ($32^\circ\text{F} - 104^\circ\text{F}$)
Storage temperature range: $-10^\circ\text{C} - 50^\circ\text{C}$ ($-4^\circ\text{F} - 122^\circ\text{F}$)
Humidity 20% - 90%-relative humidity (non-condensing)
Altitude Less than 3,000m

ELECTRICAL SPECIFICATIONS

Power Supply All power provided by the network connection using Power Over Ethernet (either mid-span injector or POE Switch, per IEEE 802.3af standard)
Operating voltage 48 volts
Power consumption < 10 watts

Your Local Distributor:



www.compumedics.com

All specifications are subject to change without notice. Please contact your Compumedics representative for latest technical information, pricing and product availability. Grael, COMPUMEDICS and the Compumedics logo are registered trademarks of Compumedics.



A1937-00